



flat 15°

Wire coil nails

loose nails

wire coil nails

- flat 15°
- flat 15° EPAL
- conical 15°

Hi-Load & Jumbo 15°


plastic sheet coil nails

plastic strip nails

paper strip nails

TOOL

| | |
|-----------------|--------------|
| BeA 550DC | MAX CN55 |
| BeA 800DC | MAX Cn80 |
| BOSTITCH N57C | MAX Cn100 |
| BOSTITCH N100CB | SENCO SCN55S |
| HITACHI NV83 | SENCO SCN65 |



Nails can be electro-galvanized.
 Layer from 8 to 13µm in yellow or grey passivation.
 Grey passivation from 8 to 13µm Cr-3.
 Hot dip galvanized min 55µm.
 Non galvanized nails are covered with a layer of yellow varnish.
 Nails can be produced from stainless steel in quality V2A (AISI 304) or V4A (AISI 316).

Shank diameter

2,1 ~ 3,8 mm
 .083" ~ .148"

Nail length

25 ~ 130 mm
 1" ~ 5 1/8"

Shank type

Smooth shank
 Screw shank
 Ring shank
 SQTW

Head diameter

5 ~ 8,5 mm
 .196" ~ .335"

| | Heads | Points |
|----------|-------|----------------------|
| LENSKOPF | | DIAMOND |
| TB | | CLINCH |
| POZI 1 | | CHISEL BP |
| POZI 2 | | NO POINT |