

flat 15°

Wire coil nails

loose nails

wire coil nails

- flat 15°
- flat 15° EPAL
- conical 15°

Hi-Load & Jumbo 15°


plastic sheet coil nails

plastic strip nails

paper strip nails

TOOL

BeA 550DC	MAX CN55
BeA 800DC	MAX Cn80
BOSTITCH N57C	MAX Cn100
BOSTITCH N100CB	SENCO SCN55S
HITACHI NV83	SENCO SCN65



Nails can be electro-galvanized.
 Layer from 8 to 13µm in grey passivation.
 Grey passivation from 8 to 13µm Cr+3.
 Hot dip galvanized min 55µm.
 Non galvanized nails are covered with a layer of yellow varnish.
 Nails can be produced from stainless steel in quality V2A (AISI 304) or V4A (AISI 316).

Shank diameter

2,1 ~ 3,8 mm
 .083" ~ .150"

Nail length











25 ~ 130 mm
 1" ~ 5 1/8"

Shank type

Smooth shank
 Screw shank
 Ring shank
 SQTW

Head diameter

5 ~ 8,5 mm
 .196" ~ .335"

	Heads	Points
LENSKOPF		DIAMOND 
TB		CLINCH 
POZI 1	 	CHISEL 
POZI 2	 	BP 
		NO POINT 