

flat 15°

## Wire coil nails

loose nails

wire coil nails

- flat 15°
- flat 15° EPAL
- conical 15°

Hi-Load & Jumbo 15°


plastic sheet coil nails

plastic strip nails

paper strip nails

### TOOL

BeA 550DC	MAX CN55
BeA 800DC	MAX Cn80
BOSTITCH N57C	MAX Cn100
BOSTITCH N100CB	SENCO SCN55S
HITACHI NV83	SENCO SCN65



Nails can be electro-galvanized.  
 Layer from 8 to 13µm in grey passivation.  
 Grey passivation from 8 to 13µm Cr+3.  
 Hot dip galvanized min 55µm.  
 Non galvanized nails are covered with a layer of yellow varnish.  
 Nails can be produced from stainless steel in quality V2A (AISI 304) or V4A (AISI 316).

### Shank diameter

2,1 ~ 3,8 mm  
 .083" ~ .150"

### Nail length

25 ~ 130 mm  
 1" ~ 5 1/8"

### Shank type

Smooth shank  
 Screw shank  
 Ring shank  
 SQTW

### Head diameter

5 ~ 8,5 mm  
 .196" ~ .335"

	Heads	Points
LENSKOPF		DIAMOND 
TB		CHISEL 
POZI 1		BP 
POZI 2		NO POINT 